



**DRAWING NOTES**

- ① Marshalls kerb 125 x 255 half battered to BS 7263: Part 1: 1994.
- ② Marshalls edging 50X150 to BS 7263: Part 1: 1994.
- ③ Marshalls Keyblock rectangular block paving 200x100x60 mm thick on well compacted sand to engineer's specification. Herringbone pattern square to edge.
- ④ Marshalls Saxon paving slabs 450x450x50 mm on mortar dabs on well compacted sand to engineer's specification.
- ⑤ Black tarmacadam on hardcore to engineer's specification.
- ⑥ Edge of parking bays: Keyblock paviors laid in soldier course pattern. Parking bays demarcation and wheelchair icon in contrasting Keyblock paviors.
- ⑦ 150x250 mm concrete foundations to engineer's specification.
- ⑧ 15mm sand:cement bed.
- ⑨ Lean mix concrete haunching.
- b ⑩ Thorn lighting bollard - Johanna - overall height 1000mm.
- c ⑪ Flush pavement mounted uplighter lighting elevation of building.

All landscaping to Landscape Architects details and specification and subject to local authority approval.  
 Refer to Landscape Architects details for service duct locations.  
 External lighting design - indicative layout shown and subject to local authority approval.  
 All finishes to be on suitable substrate to structural engineer's design and specification.  
 Refer to GNA drawing for refuse & cycle store details.

